

# OR-TEC SEPTAGE RECEIVER

## *Screen, Wash and Compact Septage*

The OR-TEC Septage Receiving Unit screens, compacts and washes screenings directly from the septage hauler. The unit is simple to install and it ensures that the septage entering the plant has been thoroughly screened. Screenings are washed, compacted and elevated to a convenient height for disposal.

The unit can be provided with perforated hole sizes ranging from 5 to 10 mm depending on the application.

### Construction material

Stainless Steel AISI 304 or AISI 316

The screw can be constructed of AISI 304 or AISI 316 stainless steel or coated micro alloy carbon steel

### Applications

- WWTP Headworks
- Septage Receiving Plants



### Features

- Quick Disconnect for Septage Haulers
- Motorized inlet valve
- Wash station provided in compacting zone
- Additional wash station in filtrate discharge zone ensures septage does not cause blockage
- Optional wash stations in screening & conveying zone
- Stainless steel liner bars increase time between replacements
- Self cleaning screen
- Available with heat tracing and insulation

Capacity:  
Up to 26,400 gph

Screen Sizing:  
5 to 10mm

Model: M



14500 Industrial Ave. South  
Maple Heights, OH 44137  
P: 216-475-5225  
F: 216-475-5229  
info@or-tec.com

[or-tec.com](http://or-tec.com)

